

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 500.38975X00

First Inventor or Application Identifier Carl I. Brunidge

Title COMPOSITE PICTURE GENERATING METHOD

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)

2. ☒ Specification [Total Pages 26]
(preferred arrangement set forth below)

- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 15]

4. Oath or Declaration [Total Pages]

- a. ☐ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
- i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

5. ☐ Microfiche Computer Program (Appendix)

6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)

- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))

8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of
(when there is an assignee) Attorney

9. ☐ English Translation Document (if applicable)

10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations

11. ☐ Preliminary Amendment

12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)

13. ☐ * Small Entity Statement(s) ☐ Statement filed in prior application
(PTO/SB/09-12) Status still proper and desired

14. ☒ Certified Copy of Priority Document(s)
(if foreign priority is claimed)

15. ☒ Other: See 1 in Addendum

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: /

Prior application information: Examiner

Group / Art Unit:

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

020457

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name

Address

City

State

Zip Code

Country

Telephone

Fax

Name (Print/Type) Carl I. Brunidge

Registration No. (Attorney/Agent) 29,621

Signature

Date 08/30/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

1. - INFORMATION UNDER 37 CRR 1.56(A) W/REFS.

115220	115221	115222	115223	115224	115225	115226	115227	115228	115229	115230	115231	115232	115233	115234	115235	115236	115237	115238	115239	115240	115241	115242	115243	115244	115245	115246	115247	115248	115249	115250	115251	115252	115253	115254	115255	115256	115257	115258	115259	115260	115261	115262	115263	115264	115265	115266	115267	115268	115269	115270	115271	115272	115273	115274	115275	115276	115277	115278	115279	115280	115281	115282	115283	115284	115285	115286	115287	115288	115289	115290	115291	115292	115293	115294	115295	115296	115297	115298	115299	115300	115301	115302	115303	115304	115305	115306	115307	115308	115309	115310	115311	115312	115313	115314	115315	115316	115317	115318	115319	115320	115321	115322	115323	115324	115325	115326	115327	115328	115329	115330	115331	115332	115333	115334	115335	115336	115337	115338	115339	115340	115341	115342	115343	115344	115345	115346	115347	115348	115349	115350	115351	115352	115353	115354	115355	115356	115357	115358	115359	115360	115361	115362	115363	115364	115365	115366	115367	115368	115369	115370	115371	115372	115373	115374	115375	115376	115377	115378	115379	115380	115381	115382	115383	115384	115385	115386	115387	115388	115389	115390	115391	115392	115393	115394	115395	115396	115397	115398	115399	115400	115401	115402	115403	115404	115405	115406	115407	115408	115409	115410	115411	115412	115413	115414	115415	115416	115417	115418	115419	115420	115421	115422	115423	115424	115425	115426	115427	115428	115429	115430	115431	115432	115433	115434	115435	115436	115437	115438	115439	115440	115441	115442	115443	115444	115445	115446	115447	115448	115449	115450	115451	115452	115453	115454	115455	115456	115457	115458	115459	115460	115461	115462	115463	115464	115465	115466	115467	115468	115469	115470	115471	115472	115473	115474	115475	115476	115477	115478	115479	115480	115481	115482	115483	115484	115485	115486	115487	115488	115489	115490	115491	115492	115493	115494	115495	115496	115497	115498	115499	115500	115501	115502	115503	115504	115505	115506	115507	115508	115509	115510	115511	115512	115513	115514	115515	115516	115517	115518	115519	115520	115521	115522	115523	115524	115525	115526	115527	115528	115529	115530	115531	115532	115533	115534	115535	115536	115537	115538	115539	115540	115541	115542	115543	115544	115545	115546	115547	115548	115549	115550	115551	115552	115553	115554	115555	115556	115557	115558	115559	115560	115561	115562	115563	115564	115565	115566	115567	115568	115569	115570	115571	115572	115573	115574	115575	115576	115577	115578	115579	115580	115581	115582	115583	115584	115585	115586	115587	115588	115589	115590	1155
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	------

- 1 -

COMPOSITE PICTURE GENERATING METHOD

BACKGROUND OF THE INVENTION

The present invention relates to a composite picture generating method of superimposing an image over a moving picture by using a computer, and more specifically to an image synthesizing method suited for synthesizing an arbitrary image moving over a moving picture and a recording medium storing an image synthesizing program.

A commonly used method for superimposing an image over a moving picture generally involves specifying positions on one or more frames at which the image is to be introduced. The area in which the image is to be fitted is generally specified by setting its boundary. An example method of automatically setting a boundary to determine an image synthesizing area in a background moving picture is described in JP-A-7-262410. This method extracts a boundary line in a real video footage, specifies with a pointing device a rough area where a user wants an image to be inserted and determines an exact area of image insertion. In the area thus determined a desired image is superimposed. Once the area is determined, the image can be superimposed over that area without needing to specify the image superimposing position for each frame.

SUMMARY OF THE INVENTION

In the conventional technology described above, when an image to be superimposed is an object that moves in a natural and smooth locus (for example, a bird flying in the sky or a goldfish in a bowl), the method that specifies the superimposing position in one or more frames has a drawback that the motion of the object does not look natural. To make the object look natural in its motion requires detailed calculations to interpolate the frames.

With another method that automatically sets a boundary to determine an area (range) in which the image is to be superimposed, locations other than those the user wants to specify as boundaries are often recognized as boundaries. This method requires high precision in the extraction of the boundary and takes time when an apparatus with a low processing power, such as personal computer for consumer, is used.

An object of the present invention is to provide a composite picture generating method that can easily synthesize an image that moves with a natural motion over a background moving picture and to provide a recording medium storing a composite picture generating program.

Another object of the present invention is to provide a composite picture generating method that supports automatically extracting from the background moving picture a movement boundary of an object to be

superimposed over the moving picture.

According to one aspect of the invention there is provided a composite picture generating method which comprises the steps of: specifying a locus of motion of
5 the image while replaying the moving picture; and synthesizing the image moving along the specified locus over the moving picture. This allows for image synthesizing wherein the movement of an object superimposed over the moving picture looks natural.

10 According to another aspect of the invention there is provided a composite picture generating method which comprises the steps of: specifying a boundary area in the moving picture; and modifying the locus of motion of the image to meet the specified boundary area
15 condition. Further, the method includes the steps of: specifying information for identifying the boundary area, or area identification information, along with the boundary area; based on the area identification information, determining an actual boundary area in the
20 moving picture being replayed; and modifying an image superimposing position. This makes the creation of an animation of an object moving in desired locations easier than when the conventional procedure is used that automatically generates a boundary to determine the area
25 of movement of the object.

Other objects, features and advantages of the present invention will become apparent from the detailed description of the embodiments of the invention taken in

conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram showing an example configuration of a computer system used in the present
5 invention.

Figure 2 is an example view of a composite picture generating program used in the embodiment.

Figure 3 is a flow chart showing overall processing of a first embodiment of the invention.

10 Figure 4 is a flow chart showing processing for specifying and determining a locus of an image in the first embodiment of the invention.

Figure 5 is an example showing how an image is drawn in the first embodiment of the invention.

15 Figure 6 is an example showing how a locus of motion of the image is drawn in the first embodiment of the invention.

Figure 7 is an example method of modifying the locus of motion of the image in the first embodiment of
20 the invention.

Figures 8A to 8C are tables showing a data structure of the locus of motion of the image in the first embodiment of the invention.

Figure 9 is a flow chart showing overall
25 processing of a second embodiment of the invention.

Figure 10 is a flow chart showing area specification processing in the second embodiment of the

invention.

Figure 11 is an example diagram showing how an area is specified in the second embodiment of the invention.

5 Figure 12 is a flow chart showing processing that limits the locus of motion of the image to within the area in the second embodiment of the invention.

Figure 13 is an example locus of motion of the image in the second embodiment of the invention.

10 Figure 14 is a table showing boundary line data in the second embodiment of the invention.

Figure 15 is a table showing position data of a locus of motion of the image in the second embodiment.

15 Figure 16 is a flow chart showing processing that modifies a locus of motion of the image by an actual area boundary line in a moving picture being played in the second embodiment of the invention.

20 Figures 17A and 17B are an example showing how a locus of motion of the image is modified by an actual area boundary line in a moving picture being played in the second embodiment of the invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Now, embodiments of the present invention will be described in detail by referring to the accompanying
25 drawings.

Figure 1 is an example configuration of a computer system used by the composite picture generating

method of the present invention. This system comprises a processor (CPU) 100, a main memory 110, a frame memory 120, a display 130, a key board 140, a pointing device such as a mouse 150, a secondary storage device 160 and a bus 170 to connect them. The main memory 110 is preloaded with a composite picture generating or image synthesizing program 111 and also stores image data 112, image locus data 113, boundary line data 114 and boundary identification information 115, all described later. The secondary storage device 160 stores in advance moving picture data 161 such as real video footage, over which an image is to be superimposed, and moving picture data 162 that was superimposed with an image.

The processor 100 starts the image synthesizing program 111 stored in the main memory 110 to display an image synthesizing program view on the display 130. Then the image synthesizing program 111 operates interactively with the user. First, the moving picture data 161 stored in the secondary storage device 160 is read out and displayed in a preview area 210 (Figure 2) of the image synthesizing program view on the display 130 through a frame memory 120. While watching the moving picture thus displayed, the user manipulates the keyboard 140 or pointing device 150 to enter image data to be synthesized into the moving picture, and specify the locus of motion of the image over the moving picture while playing the moving picture and, if necessary, a boundary line and boundary identification information (e.g., color

information) in the moving picture that restrict the movement of the image. The image data 112 entered by the user is stored in the main memory 110 and the image locus data 113 and the boundary identification information 115 are also stored in the main memory 110 in accordance with the specification of the user. Based on the stored image locus data 113 or, if necessary, on the boundary line data 114 and the boundary identification information 115, the image synthesizing program 111 superimposes the image data 112 over the moving picture data 161 while the moving picture data is played, and displays the synthesized image in the preview area of the image synthesizing program view on the display 130. The moving picture data 162 superimposed with the image is stored in the secondary storage device 160, from which it can be retrieved and used as many times as desired.

Figure 2 illustrates an image synthesizing program view 200 displayed on the display 130. In Figure 2, a field 210 is a preview area that plays a moving picture for image synthesizing. The preview area 210 is also used as an area to display the image to be superimposed on the moving picture and a locus of motion of the image. A field 220 is an area indicating the time spent to play the moving picture in the preview area 210. A cursor 221 under the field 220 indicates a currently displayed position in the field 220. A field 222 is an area to specify a playback speed. For example, "1" represents a playback at a normal speed, "1/2" a playback

at half the normal speed (slow playback), and "2" a
playback at two times the normal speed. This value can
be changed by the keyboard 140 or pointing device 150. A
field 230 is an area to specify a kind of line and a
5 color with which to draw an image in the preview area
210. A field 240 is an area (buttons) by which the user
can select either drawing of an image,
generation/modification of a locus or specification of a
superimposing area by using the pointing device 150. A
10 field 250 is to control the moving picture being played
in the preview area 210 by using the pointing device 150.
Selecting a desired icon can specify the corresponding
function, such as moving back to the head position,
stopping the playback temporarily, stopping the preview,
15 playing back and moving to the end position. A field 260
is an area to specify a moving picture to be played in
the preview area 210 either by directly inputting a file
name using the keyboard 140 or by selecting it with the
pointing device 150. A field 270 is an area (execute
20 button) to specify the execution of synthesizing by
depressing it with the pointing device 150.

First, let us explain about processing, as the
first embodiment of the invention, which superimposes an
independent image over the moving picture by manually
25 drawing an image and specifying with the pointing device
the locus of motion of the image over the moving picture
while playing the moving picture.

Figure 3 is a flow chart representing an

overall processing flow of this embodiment. Here it is assumed that the image synthesizing program 111 has already been started and that the image synthesizing program view 200 is displayed as shown in Figure 2.

- 5 Using the pointing device 150 or keyboard 140, the user chooses in the field 260 a file name of a moving picture to be superimposed with an image (step 301). Next, when the user selects a playback start button in the field 250, the corresponding moving picture data 161 is read
- 10 out from the secondary storage device 160 and displayed on the preview area 210 (step 302). The user depresses a stop button in the area 250 at a desired moving picture playback position to temporarily halt the playback of the moving picture, selects the drawing button in the field
- 15 240, selects a kind of line and a color in the field 230, and draws in the preview area 210 an image to be superimposed over the moving picture (step 303) by using the pointing device 150. When the drawn image is determined, the user selects the locus button in the
- 20 field 240, typically resumes the playing of the moving picture at a low speed, draws and determines the locus of motion of the drawn image in the preview area 210 with the pointing device 150 as the moving picture is played (step 304). The image and the locus of motion of the
- 25 image drawn in the preview area 210 are stored in the main memory 110 as the image data 112 and as the image locus data 113 representing position data at predetermined intervals. Finally, when the user

depresses the synthesize execute button in the field 270, the synthesizing of the image data 112 and the moving picture data 161 is executed based on the image locus data 113 (step 305). The synthesizing operation involves

5 pasting the image data 112 successively to the moving picture frames at corresponding positions based on the time data and position data of the image locus data 113 as the moving picture following the temporary stop is played back.

10 Figure 4 is a flow chart showing the detail of the step 304 of Figure 3. This is explained by referring to an example of Figures 5 and 6.

Figure 5 shows an image synthesizing program view 200 with an image drawn by the step 303 of Figure 3.

15 In the preview area 210, the drawn image (goldfish in this case) 500 is superimposed over the moving picture. The field 240 indicates that the drawing button is selected. The cursor 221 under the field 220 shows the point in time at which the moving picture was stopped.

20 The field 222 indicates that the moving picture was being played at the normal speed.

The user selects the locus button in the field 240 and determines the speed at which to play the moving picture (step 401). In this case, the playback speed is

25 set, for example, at half the normal playback speed (slow playback) to ensure that the locus of motion of the image can be drawn easily as the moving picture is played. Next, the user resumes the playback of the moving picture

by operating a particular key on the keyboard 140 (step 402) and at the same time moves the cursor representing the position of the image 500 in the preview area 210 to draw the locus of motion of the image (step 403). At
5 this time, the speed of the position cursor of the image is adjusted by using the pointing device 150 to match the playback speed of the moving picture. When the drawing of the desired locus of motion of the image is finished, the playback of the moving picture is ended by depressing
10 a particular key on the keyboard 140 (step 404).

Figure 6 shows the image synthesizing program view 200 at this time. In Figure 6, a reference number 600 represents a cursor representing the position of the image and 610 a locus drawn by the step 403. In Figure
15 6, the image 500 of Figure 5 is omitted for the sake of simplicity. The field 240 shows that the locus button is selected. The cursor 221 under the field 220 has moved to a time position 221' (corresponding to the front end of the locus). The playback speed in the field 222 is
20 1/2 (slow playback). The locus 610 is sampled and read in at particular time intervals or frame intervals and the position data of a series of locus points and others are stored as the image locus data 113 in the main memory 110. A frame number from which the playback is resumed
25 by the step 402 and a frame number at which the playback is ended by the step 404 are also stored.

After having drawn the motion locus of the image, the user selects the playback button in the

function selection field 250 to preview and check the locus 610 (step 405) to decide whether or not to modify the locus 610 (step 406). When the user wishes to modify the locus 610, i.e., the motion of the image, the user
5 moves to step 407. If no modification is made, the processing is ended. If, in the step 407, the user decides to redraw the locus from scratch, the user determines the start position for redrawing (step 408) and returns to step 401. When a fine adjustment is to be
10 made, the drawn locus 610 is directly modified (step 409). The redrawing or direct modification is specified by, for example, clicking on the locus button again in the field 240 or by a right-button click.

Next, a method of directly modifying or finely
15 adjusting the locus of motion of the image will be explained by referring to Figures 7 and 8. Figure 7 is an enlarged view of the previewed locus 610. Figure 8 shows a data structure of the image locus data 113 corresponding to the locus 610.

20 When the locus of the image is to be finely adjusted, a part of a series of locus points d1-d9 shown in Figure 7 needs only to be modified (by addition or deletion). In Figure 7, 700 shows a series of locus points before modification, 710 shows a series of locus
25 points with some points, such as a1 and a2, added, and 720 shows a series of locus points with some points such as d8 deleted. Here, the series of locus points represents the positions picked up at one-second

intervals (with the normal playback taken as a reference). It is of course possible to change the point pickup interval to a one-frame interval or 0.5-second interval. A table 800 in Figure 8A corresponds to the

5 before-modification series of points 700, d1-d9, of Figure 7. Here, it is possible not only to specify the locus but also to specify or modify the size (magnification factor), direction and transmittivity of the image to be superimposed. When it is desired to slow

10 down the motion of the image, some points, such as a1 and a2, are added where one wants the image to slow down, as indicated by 710 of Figure 7. As a result, data of a1 and a2 is added as shown in a table 810 of Figure 8B, changing the locus to the one where the image moves

15 slowly between d6 and d7. Conversely, when it is desired to quicken the motion of the image, a point d8 for instance is removed from where one wants the image to move quickly (although in the figure the point d8 to be deleted is shown dotted, it is actually not displayed).

20 As a result, the data corresponding to the point d8 is deleted as shown in the table 820 of Figure 8C, shortening the moving time between the points d7 and d9. Although the locus can be modified easily by manipulating the series of previewed points using the pointing device

25 150, the modification can also be done by reading the image locus data 113 from the main memory 110 and directly changing the corresponding field.

As described above, by moving the pointing

device 150 in the preview area of the image synthesizing program view, the locus of an image can be generated and modified easily.

Although this embodiment has described in the case where the playback speed when the locus is entered is constant, it is also possible to speed up or slow down the playback speed of the moving picture by an input device such as keyboard while at the same time drawing the locus with the pointing device. Further, while the flow chart of this embodiment shown in Figure 3 separates the locus drawing processing from the synthesizing of the moving picture and the superimposed image, it is of course possible to perform these processing simultaneously.

Next, a second embodiment of the present invention will be described which specifies a boundary line and area identification information in a moving picture to automatically modify the locus of the image or to automatically modify the position where the image is superimposed over the moving picture.

Figure 9 shows in flow chart an overall processing flow of this embodiment. It is assumed that the image synthesizing program 111 has already been started and the display 130 displays the image synthesizing program view 200 as shown in Figure 2. In Figure 9, steps 901 to 903 are similar to steps 301 to 303 of Figure 3 of the first embodiment. When the image to be superimposed over the moving picture has been

determined at step 903, the user selects the area button in the field 240 to specify, by using the pointing device 150 on the moving picture in the preview area 210, a boundary line and area identification information of an area in which the image is allowed to move (step 904). Next, the user selects the locus button in the field 240 and resumes the playback of the moving image at a low speed, for example, to draw and determine the locus of motion of the image as the moving picture is played (step 905). This is basically the same as the step 304 of Figure 3, except that the locus of motion of the image is automatically corrected so that it is within the area specified by the step 904. Finally, when the user depresses the synthesize execute button in the field 270, the image and the moving picture are synthesized (step 906). This, too, is basically the same as the step 305 of Figure 3 except that the position of the image is automatically corrected according to a change in the boundary line in the playback moving picture.

Figure 10 is a flow chart showing the detail of the step 904 of Figure 9. Now let us assume that the displayed state of the preview area 210 of the image synthesizing program view 200 is as shown in Figure 11. In Figure 11, reference number 1100 represents an image (ball) drawn by the step 903, 1120 represents an area A or sky, and 1121 represents an area B or ground. The range in which the image 1100 is allowed to move should be limited to the inside of the area A. The user

specifies a boundary line 1130 between the two areas with the pointing device 150 (step 1001). Next, by using the keyboard 140 or pointing device 150 the user selects representative colors and other information of the areas
5 A and B divided by the boundary line 1130 as information for identifying the areas A, B (step 1002). The boundary line and the area identification information specified by the steps 1001 and 1002 are stored in the main memory 110. They are indicated by the boundary line data 114
10 and the boundary identification information 115 in the main memory 110 of Figure 1.

Figure 12 is a flow chart of processing that automatically corrects the locus of the image so that it is within the boundary and area specified by the step 904
15 of Figure 9. The processing of Figure 12 may be executed simultaneously in synchronism with the drawing of the locus of motion of the image, or performed on the data of the image locus that has already been drawn.

First, the boundary condition for the movement
20 of the image specified by the step 904 of Figure 9 is set (step 1201). Then, for each position of a series of locus points, the processing from step 1203 on down is executed. When an (x, y) coordinate is set on the screen, a check is first made to determine whether a
25 boundary condition is set for the Y coordinate (step 1203). If it is not set, the program moves to step 1027. If it is set, comparison is made between the Y coordinate of a position of interest in a series of the locus points

and the Y coordinate of the boundary condition (step 1204). Then, it is checked whether the boundary condition is met (step 1205). If the boundary condition is met, the program proceeds to step 1207. If not, the Y coordinate of the position of interest is corrected to meet the boundary condition (step 1206) before moving to step 1207. The step 1207 checks whether a boundary condition is set for the X coordinate. If it is not set, the program returns to step 1202. If the boundary condition for the X coordinate is set, the X coordinate of a position of interest in a series of the locus points is compared with the X coordinate of the boundary condition (step 1208). Then, a checks is made to determine whether the boundary conditions is met (step 1209). If the boundary condition is met, the program returns to step 1202. If not, the X coordinate of the position of interest is corrected to meet the boundary condition (step 1210) before returning to step 1202. The step 1202 checks whether the series of locus points has all been checked. If not, the processing from step 1203 on down is repeated for the next locus point. If all the locus points are processed, the correction processing is ended. While in Figure 12 the locus points have been described to be processed in the order of Y coordinate and X coordinate for each position in the series of locus points, they can be processed in the reversed order. Alternatively, a Y coordinate group and an X coordinate group for the entire series of locus points may be

processed separately.

Next, by referring to Figures 13, 14 and 15, an example processing of steps 1204-1206 of Figure 12 associated with Y coordinate will be described. From the following explanation the processing of the steps 1208-1210 of Figure 12 associated with X coordinate can easily be understood by analogy.

Figure 13 shows the locus of motion 1310 of the image 1100 of Figure 11 drawn on the screen without considering the boundary line 1130. Figure 14 shows position coordinate data of the boundary line 1130 and Figure 15 shows position data of a series of points in the locus 1310 spaced at one-second intervals. The data shown in Figures 14 and 15 stored in the main memory 110 are actually more detailed data, but only representative positions are shown for the sake of simplicity.

For the series of points on the locus 1310, their Y coordinates plus the radius of the image (ball) 1100 must be higher (smaller) than the boundary line 1130. As shown in Figures 14 and 15, the Y coordinate of point d3 is lower (larger) than the Y coordinate of the boundary line 1130. This does not meet the condition that the image (ball) 1100 must move without crossing the boundary line 1130 (i.e., the image must move as if it is on the boundary line). So, the Y coordinate of point d3 is modified so that the lower part of the image 1100 is on the boundary line 1130. This synthesizes the image 1100 so that it appears to move on the boundary line 1130

near the point d3.

Figure 16 shows a flow chart of processing which, in the step 906 of Figure 9 for synthesizing the moving picture and the image, automatically modifies the position data of the locus points of the image when the boundary area in the moving picture being played changes.

First, the area boundary line coordinate data and area identification information such as typical colors of areas, specified by the step 904 of Figure 9, are set (step 1601). Then, the position data of the series of locus points of the image (image locus data) is retrieved as the moving picture is played and, for each locus point, the processing from step 1603 on down is executed. First, based on the area identification information, the actual area boundary line coordinate at the present time in the frame of the moving picture being played is determined (step 1603). A difference between the actual area boundary line coordinate and the boundary line coordinate set by the step 1601 is calculated (step 1604). The difference value may be obtained by determining a reference position for the real and specified boundary lines in advance and calculating their difference at the reference position, or by determining the differences between the boundary lines at individual positions and calculating their average. This difference value is added to the coordinate value of the position data for the locus point of interest to modify the position coordinate of the image and synthesize the

moving picture and the image (step 1605) before returning to step 1602. In step 1602, it is checked whether the series of the locus points has all been processed. If all the locus points are not processed, the steps 1603-
5 1605 are executed for each of the remaining locus points in each frame of the moving picture being played. When all the points are processed, the image synthesizing processing is ended.

Next, by referring to Figures 17A and 17B, an
10 example processing of step 1605 of Figure 16 will be explained. Figure 17A represents a state before modification and Figure 17B represents a state after modification. Reference number 1130 represents an area boundary line specified by the step 904 of Figure 9 and
15 1710 represents an actual area boundary line in the currently replayed moving picture that is determined by the step 1603 of Figure 16. The value d is the difference between these two boundary lines. The coordinate positions of the image 1100 as shown in Figure
20 17A appears unnatural. Thus, in step 1605 of Figure 16, the position coordinates of the series of locus points are moved upward by the difference value d to obtain a natural synthesized image as shown in Figure 17B.

In the above embodiments, we have described
25 example cases where a handwritten image is moved over the moving image. The image to be superimposed can be not just a handwritten static image but a prepared animation or moving picture. When specifying the locus of an

image, it is possible to specify or modify not only the position but also the size, direction and transmittivity of the image to be superimposed.

In the embodiments the user draws the locus of motion of the image. When an object is moved over the moving picture at a constant speed or at a constant acceleration for example, specifying the initial position, direction and speed (unit movement) of the moving object can automatically determines the locus of motion of the object as the moving picture is played. In this case, the user does not need to draw the locus. Of course, in this case too, it is possible to make a modification similar to that described in the preceding embodiments by specifying the boundary area in which the object is allowed to move and the boundary identification information.

The image synthesizing program for implementing the image synthesizing method of this embodiment can be described in a computer-implemented language and stored in computer-readable recording media, such as floppy disk, CD-ROM and memory card, for transfer.

As described above, this invention allows an arbitrary image with a natural motion to be superimposed over a moving picture without requiring complex computations, making it easy to create an animation in which the image can be made to move in a desired location as by using a pointing device.

WHAT IS CLAIMED IS:

1. A composite picture generating method for superimposing an image over a moving picture comprising the steps of:

specifying a locus of motion of the image as the moving picture is played; and

synthesizing the image moving along said specified locus over the moving picture.

2. A composite picture generating method according to claim 1, comprising the steps of:

specifying a boundary area in the moving picture; and

modifying the locus of motion of the image so as to satisfy a condition defining said specified boundary area condition.

3. A composite picture generating method according to claim 2, comprising the steps of:

specifying information for identifying the boundary area along with the boundary area;

determining an actual boundary area in the played-back moving picture based on the specified area identification information; and

modifying an image superimposing position of said image based on the determined actual boundary area.

4. A computer-readable recording medium storing a program for implementing the composite picture generating method of claim 1 by a computer.

5. A computer-readable recording medium storing a

program for implementing the composite picture generating method of claim 2 by a computer.

6. A computer-readable recording medium storing a program for implementing the composite picture generating method of claim 3 by a computer.

7. A composite picture generating method for superimposing an image over a moving picture, executed by using a computer, said method comprising the steps of:

```

        displaying the moving picture on a screen of a
display from moving picture data;

```

drawing a desired locus of motion over the moving picture on the display screen as the moving picture is played, to generate the locus of motion of the image to be superimposed over the displayed moving picture; and

combining said image and said displayed moving picture in accordance with the drawn locus to generate a composite moving picture in the form of data.

8. An image synthesizing method according to claim 7, wherein said step of drawing the locus of motion of the image comprises a step of variably changing a playback speed of the moving picture displayed on the screen.

9. An image synthesizing method according to claim 7, wherein said step of drawing the locus of motion of the image comprises a step of drawing the locus of motion over the displayed moving picture with a pointing device.

10. A composite picture generating method according

•

•

drawing a desired locus of motion over the moving picture on the display screen as the moving picture is played, to generate the locus of motion of the

image to be superimposed over the displayed moving picture; and

superimposing said image over the moving picture according to the drawn locus to generate a synthesized moving picture in the form of data.

15. A software according to claim 14, comprising a step of specifying a motion boundary area for the superimposed image on the displayed moving picture and modifying the drawn locus so as to satisfy a condition defining the specified motion boundary area.

16. A software according to claim 15, comprising a step of specifying area identification information for identifying the boundary area, extracting an actual boundary of the replayed moving picture according to the area identification information, and modifying a superimposing position of said image on the moving picture.

[illegible][illegible]

FIG. 1




FIG. 2

200 IMAGE SYNTHESIZING PROGRAM VIEW




FIG. 3




FIG. 4




FIG. 5

200 IMAGE SYNTHESIZING PROGRAM VIEW




FIG. 6

200 IMAGE SYNTHESIZING PROGRAM VIEW






FIG. 7

BEFORE
MODIFICATION



ADDED



DELETED




FIG. 8 A

800

POINT	TIME	POSITION	SIZE	DIRECTION	TRANSMITTIVITY
d1	0:00:10:00	(240,100)	1	0°	0
d2	0:00:11:00	(235,105)	1	0°	0
d3	0:00:12:00	(210,110)	1	15°	0
d4	0:00:13:00	(190,130)	1	0°	0
d5	0:00:14:00	(235,150)	1	180°	0
d6	0:00:15:00	(280,200)	1	180°	0
d7	0:00:16:00	(210,250)	1	15°	0
d8	0:00:17:00	(195,255)	1	15°	0
d9	0:00:18:00	(180,255)	1	0°	0

FIG. 8 B

POINT	TIME	POSITION			
d1	0:00:10:00	(240,100)			
⋮	⋮	⋮			
d6	0:00:15:00	(240,100)			
a1	0:00:16:00	(280,200)			
a2	0:00:17:00	(240,230)			
d7	0:00:18:00	(210,250)			
⋮	⋮	⋮			

FIG. 8 C

POINT	TIME	POSITION			
d1	0:00:10:00	(240,100)			
⋮	⋮	⋮			
d6	0:00:15:00	(240,100)			
d7	0:00:16:00	(210,250)			
d9	0:00:17:00	(180,255)			

FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

x	0		130	170	190	250		280	340	350
y	180		175	165	175	170		183	189	185

FIG. 15

POINT	TIME	POSITION
d1	0:00:10:00	(130,170)
d2	0:00:11:00	(170,100)
d3	0:00:12:00	(190,100)
d4	0:00:13:00	(250,210)
d5	0:00:14:00	(280,160)
d6	0:00:15:00	(340,170)
d7	0:00:16:00	(350,175)

FIG. 16




FIG. 17 A




FIG. 17 B

